

PFH 26 | 26 mm SDS-plus 2-mode fixing hammer

Article: 4933428230



- Most compact, slimline fixing hammer available in its class.
- Unmatched performance with 2.4 J blow energy and 4500 bpm.
- Lowest vibration at drilling into concrete: only 13.5 m/s².
- Extreme Milwaukee® durability thanks to Integrated metal block technology.
- Innovative and patented internal weight reduction technology.
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal.
- Brush rotation ring (for same power in forward & reverse action).

	PFH 26
Sound pressure level (dB(A))	92
Sound pressure level uncertainty (dB(A))	3
Sound power level (dB(A))	103
Sound power level uncertainty (dB(A))	3
Vibration drilling into concrete [m/s ²]	13.5
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Supplied in	Kitbox
Vibration drilling (m/s ²)	13.5
Vibration chiseling (m/s ²)	8.5
Article Number	4933428230
Weight (kg)	2.4
Power input (W)	725
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. drilling concrete (mm)	26
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Blow energy (EPTA)(J)	2.4